

## PUN 3X2 SILVER

PRODUCT  
Image  
Unavailable

PRODUCT  
Image  
Unavailable

Polyuretan slang 3 x 2 mm, ljusgrå

Betyg: Inte betygsatt ännu

**Pris**

Pris 7,95 kr

Pris utan moms 6,36 kr

Rabatt

Momsbelopp 1,59 kr

[Ställ en fråga om denna produkt](#)

### Beskrivning

Technical data

Hose Ø outside x inside [mm] 3 x 2

colour light grey

Operating pressure [bar] 10

Min. bend radius [mm] 10

Note RoHS-compliant

Weight 5.4 g / m

Further information

Packing unit 50

Customs duty number: 39173900

Description

Advantages:

\*small bend radius due to being particularly flexible, \*\*very good low temperature flexibility and reset characteristics, \*kink and abrasion resistant, \*\*resistant to aliphatic hydrocarbons and most lubricants, \*ageing resistance in oxygen, \*\*drag line compatible (min. bend radius corresponds to 10 x outer diameter)

Material:

Polyester polyurethane

# PUN polyuretanrör utv tolerans: PUN 3X2 SILVER

---

Temperature range:

-35°C to max. +60°C

Shore hardness:

97 A

Roll length:

50 m

Reference values for the pressure utilisation under temperature loading:

to +20°C: 100%, +30°C: 80%, +40°C: 68%, +50°C: 58%, +60°C: 50%

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.