

## PUN 4X2,5 KLAR



Polyuretan slang 4 x 2.5 mm, klar

Betyg: Inte betygsatt ännu

### Pris

Pris 8,91 kr

Pris utan moms 7,13 kr

Rabatt

Momsbelopp 1,78 kr

[Ställ en fråga om denna produkt](#)

## Beskrivning

### Technical data

Hose Ø outside x inside [mm] 4 x 2.5

colour clear

Operating pressure [bar] 13

Min. bend radius [mm] 10

Note RoHS-compliant

Weight 12 g / m

### Further information

Packing unit 50

Customs duty number: 39173900

### Description

### Advantages:

\*small bend radius due to being particularly flexible, \*\*very good low temperature flexibility and reset characteristics, \*kink and abrasion resistant, \*\*resistant to aliphatic hydrocarbons and most lubricants, \*ageing resistance in oxygen, \*\*drag line compatible (min. bend radius corresponds to 10 x outer diameter)

### Material:

Polyester polyurethane

# PUN polyuretanrör utv tolerans: PUN 4X2,5 KLAR

---

Temperature range:

-35°C to max. +60°C

Shore hardness:

97 A

Roll length:

50 m

Reference values for the pressure utilisation under temperature loading:

to +20°C: 100%, +30°C: 80%, +40°C: 68%, +50°C: 58%, +60°C: 50%

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.