PUN 4X2,5 SILVER





Polyuretan slang 4 x 2.5 mm, ljusgrå

Betyg: Inte betygsatt ännu
Pris
Pris 8,94 kr

Pris utan moms 7,15 kr

Rabatt

Momsbelopp 1,79 kr

Ställ en fråga om denna produkt

Beskrivning

Technical data

Hose Ø outside x inside [mm] 4 x 2.5

colour silver

Operating pressure [bar] 13

Min. bend radius [mm] 10

Note RoHs-compliant

Weight 12 g / m

Further information

Packing unit 50

Customs duty number: 39173900

Description

Advantages:

•small bend radius due to being particularly flexible, •very good low temperature flexibility and reset characteristics, •kink and abrasion resistant, •resistant to aliphatic hydrocarbons and most lubricants, •ageing resistance in oxygen, •drag line compatible (min. bend radius corresponds to 10 x outer diameter)

Material:

Polyester polyurethane

PUN polyuretanrör utv tolerans: PUN 4X2,5 SILVER

Temperature range:

-35°C to max. +60°C

Shore hardness:

97 A

Roll length:

50 m

Reference values for the pressure utilisation under temperature loading:

to +20°C: 100%, +30°C: 80%, +40°C: 68%, +50°C: 58%, +60°C: 50%

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.