1 TF 6





PTFE slang med rostfritt flätat hölje DN 6

Betyg: Inte betygsatt ännu
Pris
Pris 532,74 kr

Pris utan moms 426,19 kr

Rabatt

Momsbelopp 106,55 kr

Ställ en fråga om denna produkt

Beskrivning

Technical data

DN [mm] 6

Hose Ø inside [mm] 6.45 - 6.96

Hose Ø external [mm] 8.83 - 9,86

PTFE wall thickness [mm] 0,75

Operating pressure [bar] 224

Burst pressure [bar] 672

Min. bend radius [mm] 67

Further information on 1TF6

Weight 105 g / m

GTIN 4050571186760

Customs duty number 39173100

RoHS compliant Yes

Description - PTFE hose with stainless steel braiding DN 6

PTFE slang med rostfritt flätat hölje: 1 TF 6

Materials:

Wire braiding: 1.4306, Inner tube: PTFE

Temperature range:

-60°C bis +220°C

Operating pressure:

at -60°C to max. +120°C: 100% of the table value, above +120°C: minus 1% of the table value for each additional degree of temperature

Tried and tested for usage in:

Food processing, laboratory and medical equipment, vulcanising presses, steam-iron machines as well as cleaning devices, where a high chemical resistance, thermal stability, elasticity and weather resistance are needed.