# 1 TF 16





PTFE slang med rostfritt flätat hölje DN 16

Betyg: Inte betygsatt ännu
**Pris**
Pris 1.513,11 kr

Pris utan moms 1.210,49 kr

Rabatt

Momsbelopp 302,62 kr

Ställ en fråga om denna produkt

Beskrivning

**Technical data**

DN [mm] 16

Hose Ø inside [mm] 16.40 - 17.12

Hose Ø external [mm] 19.20 - 20.50

PTFE wall thickness [mm] 0,90

Operating pressure [bar] 114

Burst pressure [bar] 345

Min. bend radius [mm] 178

Further information on 1TF16

Weight 390 g / m

GTIN 4050571186739

Customs duty number 39173100

RoHS compliant Yes

Description - PTFE hose with stainless steel braiding DN 16

# PTFE slang med rostfritt flätat hölje: 1 TF 16

**Materials**:

Wire braiding: 1.4306, Inner tube: PTFE

**Temperature range:**

-60°C bis +220°C

**Operating pressure:**

at -60°C to max. +120°C: 100% of the table value, above +120°C: minus 1% of the table value for each additional degree of temperature

**Tried and tested for usage in:**

Food processing, laboratory and medical equipment, vulcanising presses, steam-iron machines as well as cleaning devices, where a high chemical resistance, thermal stability, elasticity and weather resistance are needed.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.