

G 4 LL MSV



Rak skarv skärring fitting 4 LL, nickelplätterad mässing

Betyg: Inte betygsatt ännu

Pris

Pris 51,61 kr

Pris utan moms 41,29 kr

Rabatt

Momsbelopp 10,32 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

Model series very light model series

Tube Ø outer [mm] 4 LL

Union nut thread M 8 x 1

Operating pressure with hard copper tube [bar] 100

Temperature range [°C] -60 to +300

Further information on G-4LLMSV

Weight 15 g / Pcs

GTIN 4050571312534

Customs duty number 74122000

RoHS compliant Yes

Description - Straight cutting ring fitting 4 LL, nickel-plated brass

Materials:

Body: nickel-plated brass, cutting ring: brass

Temperature range:

-60°C up to max. +300°C (swivel screw connections: -20°C up to max. +80°C)

Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

Note:

When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.