G 8 LL MSV



Rak skarv skärring fitting 8 LL, nickelplätterad mässing

Betyg: Inte betygsatt ännu
Pris
Pris 67,43 kr

Pris utan moms 53,94 kr

Rabatt

Momsbelopp 13,49 kr

Ställ en fråga om denna produkt

Beskrivning

Technical data

Model series very light model series

Tube Ø outer [mm] 8 LL

Union nut thread M 12 x 1

Operating pressure with hard copper tube [bar] 100

Temperature range [°C] -60 to +300

Further information on G8LLMSV

Weight 28 g / Pcs

GTIN 4050571312756

Customs duty number 74122000

RoHS compliant Yes

Description - Straight cutting ring fitting 8 LL, nickel-plated brass

Materials:

Body: nickel-plated brass, cutting ring: brass

Raka skarvar: G 8 LL MSV

Temperature range:

-60°C up to max. +300°C (swivel screw connections: -20°C up to max. +80°C)

Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

Note:

When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.