

GAI 10 LR 3/8 MSV



Rak skärningskoppling. 10 L-G 3/8", nickelplätterad mässing

Betyg: Inte betygsatt ännu

Pris

Pris 120,46 kr

Pris utan moms 96,37 kr

Rabatt

Momsbelopp 24,09 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

Model series light model series

Tube Ø outer [mm] 10 L

Female thread G 3/8"

Operating pressure with hard copper tube [bar] 115

Temperature range [°C] -60 to +300

Further information on GAI10LR3/8MSV

Weight 48 g / Pcs

GTIN 4050571480165

Customs duty number 74122000

RoHS compliant Yes

Description - Screw cutting ring fit. 10 L-G 3/8", nickel-plated brass

Materials:

Body: nickel-plated brass, cutting ring: brass

Raka inv. gängade kopplingar: GAI 10 LR 3/8 MSV

Temperature range:

-60°C up to max. +300°C (swivel screw connections: -20°C up to max. +80°C)

Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

Note:

When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.