

4 SP 6



4 SP hydraullang, EN 856, DN 6

Betyg: Inte betygsatt ännu

Pris

Pris 734,56 kr

Pris utan moms 587,65 kr

Rabatt

Momsbelopp 146,91 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

DN [mm] 6

Hose Ø inside [mm] 6,4

Hose Ø external [mm] 17,6

Operating pressure [bar] 485

Burst pressure [bar] 2400

Min. bend radius [mm] 100

Size parameter 4

Further information on 4SP6

Weight 800 g / m

GTIN 4050571199081

Customs duty number 40092100

RoHS compliant Yes

Description - 4 SP hose, EN 856, DN 6

4 SP - 4 dubbel stålarmering, EN 856: 4 SP 6

Materials:

Synthetic internal and external rubber

Temperature range:

-40? to max. +100?, temporary up to max. +125?

Operating range:

high pressure hydraulic systems

Resistance:

Hydraulic oils on basis of mineral oil, air*, water, lubricants and fuels, bio oils

Delivered as:

Due to the manufacturing process we cannot exclude that the goods will be supplied in pieces. We attempt to deliver max. 3 pieces, where none of the pieces is shorter than 3 meters.

*hose must be pickled

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.