# 4 SP 12



4 SP hydraulslang, EN 856, DN 12

Betyg: Inte betygsatt ännu
**Pris**
Pris 800,11 kr

Pris utan moms 640,09 kr

Rabatt

Momsbelopp 160,02 kr

Ställ en fråga om denna produkt

Beskrivning

**Technical data**

DN [mm] 12

Hose Ø inside [mm] 12,7

Hose Ø external [mm] 24,2

Operating pressure [bar] 420

Burst pressure [bar] 1750

Min. bend radius [mm] 120

Size parameter 8

**Further information on 4SP12**

Weight 900 g / m

GTIN 4050571199036

Customs duty number 40092100

RoHS compliant Yes

Description - 4 SP hose, EN 856, DN 12

# 4 SP - 4 dubbel stålarmering, EN 856: 4 SP 12

**Materials**:

Synthetic internal and external rubber

**Temperature range**:

-40? to max. +100?, temporary up to max. + 125?

**Operating range**:

high pressure hydraulic systems

**Resistance**:

Hydraulic oils on basis of mineral oil, air*, water, lubricants and fuels, bio oils

**Delivered as**:

Due to the manufacturing process we cannot exclude that the goods will be supplied in pieces. We attempt to deliver max. 3 pieces, where none of the pieces is shorter than 3 meters.

*hose must be pricked

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.