# 4 SP 25



4 SP hydraulslang, EN 856, DN 25

Betyg: Inte betygsatt ännu
**Pris**
Pris 1.318,91 kr

Pris utan moms 1.055,13 kr

Rabatt

Momsbelopp 263,78 kr

Ställ en fråga om denna produkt

Beskrivning

**Technical data**

DN [mm] 25

Hose Ø inside [mm] 25,4

Hose Ø external [mm] 39,0

Operating pressure [bar] 320

Burst pressure [bar] 1400

Min. bend radius [mm] 340

Size parameter 16

**Further information on 4SP25**

Weight 2 kg / m

GTIN 4050571199067

Customs duty number 40092100

RoHS compliant Yes

Description - 4 SP hose, EN 856, DN 25

# 4 SP - 4 dubbel stålarmering, EN 856: 4 SP 25

**Materials**:

Synthetic internal and external rubber

**Temperature range**:

-40? to max. +100?, temporary up to max. + 125?

**Operating range**:

high pressure hydraulic systems

**Resistance**:

Hydraulic oils on basis of mineral oil, air*, water, lubricants and fuels, bio oils

**Delivered as**:

Due to the manufacturing process we cannot exclude that the goods will be supplied in pieces. We attempt to deliver max. 3 pieces, where none of the pieces is shorter than 3 meters.

*hose must be pricked

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.