CK 149 MSV **



Rak koppling G 1/4"-11,6x9mm, Nickelplätterad mässing

Betyg: Inte betygsatt ännu
Pris
Pris 41,98 kr

Pris utan moms 33,58 kr

Rabatt

Momsbelopp 8,40 kr

Ställ en fråga om denna produkt

Beskrivning

Technical data

Material Nickel-plated brass

seal NBR

Screw-in thread G 1/4"

Hose Ø outside x inside [mm] 11,6x9

Operating pressure [bar] -0.95 to 20

Temperature range [°C] -20 to +80

Further information on CK149MSV

Weight 30 g / Pcs

GTIN 4050571233617

Customs duty number 74122000

RoHS compliant Yes

Description - Straight screw connection G 1/4"-11,6x9mm, Nickel-plated brass

Type brass nickel-plated (NBR & FKM seal)

Operating pressure:

-0.95 to 20 bar

Temperature range:

-20°C up to max. +80°C, with FKM seal to max. +150°C

aluminium type

Operating pressure:

-0.99 to 15 bar

Temperature range:

-15°C to max. +70°C

Plastic type

Operating pressure:

-0.99 to 10 bar

Temperature range:

-10°C to max. +60°C

*Threaded body in galvanised steel, union nuts in aluminium, **no elastomer seal

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.